






















Cabling

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter	Wire Gauge	Ratings/Certifications
CB102	 Red Teflon®	Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.175 in (4,5 mm)	AWG = 20	 RoHS PLENUM 
			Compatible Connectors: A2A, A2B, A2E, A2F, A2P, A2R, B2A, B2B, B2R, D2H, D2J, E, EMPP, EX, F, FX, J2A, J2P, L, R2C, Z					
CB103	 Black Polyurethane	Permanent Monitoring / Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.245 in (6 mm)	AWG = 20	 RoHS
			Compatible Connectors: A2A, A2E, A2P, A2R, B2A, B2R, D2C, D2CG, D2D, D2H, E, EMPP, EX, F, FX, J2A, J2C, J2P, K2C, L, R2C, Z					
CB110	 Black Polyurethane, Light Weight	Permanent Monitoring / Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.175 in (4,5 mm)	AWG = 20	 RoHS
			Compatible Connectors: A2A, A2E, A2P, A2R, B2A, B2R, D2C, D2CG, D2D, D2H, E, EMPP, EX, F, FX, J2A, J2C, J2P, K2C, L, R2C, Z					
CB111	 Yellow Teflon®	Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	400°F (204°C)	.190 in (4,8 mm)	AWG = 20	 RoHS PLENUM 
			Compatible Connectors: A2A, A2B, A2E, A2F, A2P, A2R, B2A, B2B, B2R, D2C, D2CG, D2D, D2H, D2J, E, EMPP, EX, F, FX, J2A, J2C, J2P, K2C, L, R2C, Z					
CB104	 Black Polyurethane, Coiled	Portable Measurement	2 Conductor	Braided Shield	250°F (121°C)	.210 in (5,3 mm)	AWG = 22	 
			Compatible Connectors: D2C, D2CG, D2D, D2H, E, EX, F, FX, J2C, K2C, L, R2C, Z					
CB108	 Black Polyurethane, Light Weight, Coiled	Portable Measurement	2 Conductor	Braided Shield	250°F (121°C)	.170 in (4 mm)	AWG = 24	 
			Compatible Connectors: D2C, D2CG, D2D, D2H, E, EX, F, FX, J2C, K2C, L, R2C, Z					
CB193	 Blue Polyurethane	Permanent Monitoring / Portable Measurement	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.175 in (4,5 mm)	AWG = 20	 RoHS
			Compatible Connectors: A2A, A2E, A2P, B2A, B2R, D2C, D2CG, D2D, D2H, E, EMPP, EX, F, FX, J2A, J2C, J2P, K2C, L, R2C, Z					
CB112	 White Teflon®	Permanent Monitoring	3 Conductor	Foil with Drain Wire	400°F (204°C)	.175 in (4,5 mm)	AWG = 20	 RoHS PLENUM 
			Compatible Connectors: A3A, A3B, A3E, A3F, A3P, A3R, B3A, B3B, B3R, E2C, F2C, G3H, L, Z					

* Teflon® is a registered trademark of DuPont.

Note: Bulk cable purchase discount is available for cable purchased in 500 or 1000 ft. reels