

LP332 Series

Loop Power Sensor, Acceleration, 4-20 mA Output, with C° Temperature Output, Top Exit



PROTECTION & RELIABILITY INSTRUMENTS



Product Features


Acceleration Output for Higher Frequency Applications

- ▶ Peak and RMS Outputs Available
- ▶ Enables Vibration Alarms for Process Control
- ▶ Outputs to PLC, DCS, SCADA

LP332-XXX-1E

3 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common
C	(+) Temperature Voltage




Built To Order

LP332-XXX-2E

Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire




Built To Order

LP332-XXX-3E

Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP332	M/LP332	<u>Physical</u>		
Temperature Output	10 mV/°C		Sensing Element	PZT Ceramic	
	within the range 2.5°C - 100°C		Sensing Structure	Shear Mode	
Tolerance: 4 mA	(± 5%)		Weight	2.0 oz	86 grams
Tolerance: 20 mA	(± 10%)		Case Material	316L Stainless Steel	
Tolerance: Temperature	(± 5°C)		Mounting	1/4-28	
<u>Electrical</u>			Connector (Non-Integral)	3 Pin MIL-C-5015	
Settling Time	<30 Seconds		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Voltage Source (IEPE)	15-30 VDC		Mounting Hardware	1/4-28 Stud	M6x1 Adapter Stud
Case Isolation	>10 ⁸ ohm		Calibration Certificate	Current Output @ 100 Hz	
<u>Environmental</u>					
Temperature Range	-40 to 185°F	-40 to 85°C			
Electromagnetic Sensitivity	CE				
Sealing	Welded, Hermetic				
Submersible Depth	200 ft.	60 m			

Ordering Information

<input type="checkbox"/> /LP332 - <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> - <input type="checkbox"/> <input type="checkbox"/> / <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> / <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>						
Stud Type Blank = 1/4-28 M = M6x1	Measurement Range 0 = 0-1 g 2 = 0-2 g 5 = 0-5 g 10 = 0-10 g 20 = 0-20 g	Range Type P = Peak R = RMS	Frequency Range ±3 dB 1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-600000 CPM (3-10000 Hz) 4 = 180-3000000 CPM (3-5000 Hz)	Style 1E = 2 Pin MIL C-5015 2E = Integral Cable 3E = Armor Jacket	Integral Options / <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> / <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	
					Armor Length (Integral)* 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m	Cable Length (Integral)* 010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m
*Custom Lengths Available Upon Request						

Lifetime Warranty on Materials & Workmanship

www.ctconline.com | sales@ctconline.com | 585-924-5900