



A DIVISION OF DAKOTA FLUID POWER, INC.

D SERIES DRUM TOPPER

Compact & Portable!

Compact and portable, the DTD Drum Topper is designed to fit perfectly on top of a 55-gallon drum. When portability and convenience is of the utmost importance, the Drum Topper has your back. With the ability to be used horizontally or vertically, our drum topper is the most versatile in the industry. It has the ability to filter oil viscosities up to 600cSt (ISO VG 680) at 100°F within ambient temperature ranges of -15°F to 150°F. All Y2K products are 100% customizable upon request.

Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Dispensing new oil



D SERIES DRUM TOPPER

Performance:

For filtering mineral and synthetic based oils (hydraulic oils, gear oils and turbine oils) with a maximum operating viscosity range of ISO VG 690 (3000ssu/648cSt) at 100°F within ambient temperature ranges of -15°F to 150°F

Standard Features:

Frame:	Heavy duty aluminum frame
Paint:	Multiple color options available
Motor:	1/4HP, 1/2HP & 1HP, 115vac, 60Hz or Pneumatic
Filter Heads:	Medium pressure, cast aluminum heads
Pump:	Heavy duty, gear pump. Available in 1, 2.5 and 10 GPM
Connections:	Various quick connect options available
Hoses:	7ft. Clear PVC, steel reinforced hose or hydraulic hose
Power Switch:	On/Off Toggle Switch
Cord:	4ft. cord
Filter Indicators:	Slide bar indicators trigger at 50psid when elements need to be changed
Pump Relief:	Opens at 150psi
Weight:	Approx. 45 lbs (will vary depending on options)

Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1066	β4(c)=2000	14/12/9 - 13/11/8
P1065	β7(c)=2000	18/16/13 - 15/13/10
P1063	β10(c)=1000	19/17/14 - 18/16/13
P1064	β25(c)=2000	20/18/15 - 19/17/14
P1048WR	Water Removal	

All D Series elements measure 5" x 14".

Components:

Item Number	Description	Qty.
1	Frame	1
2	Motor	1
3	Pump	1
4	Filter Head	2
5	Filter Element	2
6	Filter Indicator	2
7	Switch On/Off	1
8	Cord	1

