

## M SERIES DRUM TOPPER

### Compact & Portable!

Compact and portable, the DTM Drum Topper is designed to fit perfectly on top of a 55-gallon drum. When portability and convenience is of the utmost importance, the Drum Topper has your back. With the ability to be used horizontally or vertically, our drum topper is the most versatile in the industry. It has the ability to filter oil viscosities up to 600cSt (ISO VG 680) at 100°F within ambient temperature ranges of -15°F to 150°F. All Y2K products are 100% customizable upon request.

### Typical Applications:

- Pre-filtering new oil
- Transferring oils
- Topping off reservoirs
- Dispensing new oil



# M SERIES DRUM TOPPER

## Performance:

For filtering mineral and synthetic based oils (hydraulic oils, gear oils and turbine oils) with a maximum operating viscosity range of ISO VG 690 (3000ssu/648cSt) at 100°F within ambient temperature ranges of -15°F to 150°F.

## Standard Features:

<b>Frame:</b>	Heavy duty aluminum frame
<b>Paint:</b>	Multiple color options available
<b>Motor:</b>	1/4HP, 1/2HP & 1HP, 115vac, 60Hz or Pneumatic
<b>Filter Heads:</b>	Aluminum heads
<b>Pump:</b>	Heavy duty gear pump. Available in 1, 2, 5 and 10 GPM
<b>Connections:</b>	Various quick connect options available
<b>Hoses:</b>	7ft. Clear PVC, steel reinforced hose or hydraulic hose
<b>Power Switch:</b>	Sealed on/off toggle switch
<b>Filter Indicators:</b>	Pop up indicator triggers at 50 psid when elements need to be changed.
<b>Pump Relief:</b>	Opens at 150psi
<b>Weight:</b>	Approx. 45 lbs (will vary depending on options)

## Replacement Elements:

Part Number	BETA Rating	Desired Cleanliness Level (ISO Code)
P1068	β3(c)=1000	14/12/9 - 13/11/8
P1069	β6(c)=1000	17/15/12 - 14/12/9
P1070	β10(c)=1000	18/16/13 - 17/15/12
P1071	β25(c)=1000	21/19/16 - 20/18/15
P1072WR	Water Removal	

All M Series elements measure 5" x 10".

## Components:

Item Number	Description	Qty.
1	Frame	1
2	Motor	1
3	Pump	1
4	Filter Head	2
5	Filter Element	2
6	Filter Indicator	2
7	Switch On/Off	1
8	Cord	1

