

AC935 Series

Nonincendive, CSA North America Class 1, Division 2, ATEX/IECEx Zone 2
Approved Accelerometer, Top Exit 2 Pin Connector, 100 mV/g, ±10%



Regulatory Information

CSA 221421

Ex nA IIC T3/T4

DIP A22 IP6X T150°C (T-Code = T3) or T105°C (T-Code = T4)

AEx nA IIC T3 / T4, CI, ZONE 2

AEx tD 22, IP6X T150°C (T-Code=T3) or T105°C (T-Code=T4)

CI D2, Gr A-D, CII D2, Gr F,G, CIII

OPERATING TEMP CODE: T3

AMBIENT TEMP RANGE = -40°C TO +125°C

OPERATING TEMP CODE: T4

AMBIENT TEMP RANGE = -40°C TO +80°C

Control Drawing INS10035

Vmax = 28VDC, Imax = 100mA

CSACa 24ATEX1004X

IECEx CSA 240015X

Ex ec IIC T* °C Gc

Ex tc IIIC T135 °C Dc

Temperature code for gas for ambient range:

T4 for ambient range of -40 °C to +80 °C

T3 for ambient range of -40 °C to +121 °C

V = 28VDC I = 10mA


Approved Cabling: CB102, CB103*, CB111, CB190*, CB193*, CB296

(*Approved for Use in T4

Applications Only)


AC935-1A 2 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



AC935-2C CB190 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC935-3C CB296 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC935	M/ or M8/AC935	<u>Environmental</u>		
Sensitivity (±10%)	100 mV/g		Operating Temperature Range	-40 to 250 °F	-40 to 121 °C
Frequency Response (±3dB)	30-900,000 CPM	0.5-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	60-600,000 CPM	1.0-10000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 80 g, peak		Sealing	Welded, Hermetic	
<u>Electrical</u>			<u>Physical</u>		
Settling Time	<3.5 Seconds		Sensing Element	PZT Ceramic	
Voltage Source	18-28 VDC		Sensing Structure	Shear Mode	
Constant Current Excitation	2-10 mA		Weight	3.2 oz	91 grams
Spectral Noise @ 10 Hz	30 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 100 Hz	19 µg/√Hz		Mounting Thread	1/4-28 Blind Tapped Hole	
Spectral Noise @ 1000 Hz	15 µg/√Hz		Connector (Non-Integral)	2 Pin MIL-C-5015	
Output Impedance	<100 ohm		Resonant Frequency	1,380,000 CPM	23000 Hz
Bias Output Voltage	10-14 VDC		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware Supplied	1/4-28 Stud	M6x1 or M8x1.25 Adapter Stud
			Calibration Certificate	CA10	

Typical Frequency Response

